

[Home](#) ▶ [Equipment](#) ▶ [Excavators](#) ▶ [Compact Excavators](#) ▶ E35

# E35

## Compact Excavator



The time-tested E35 is our best-selling compact excavator, delivering proven performance on the most demanding jobsites. The zero-tail-swing E35 is designed with practical features that enhance durability, simplify routine maintenance and take operator productivity to a new level.

- Refined, low-effort joysticks
- Exclusive in-track swing frame
- Dual-flange roller system
- Reduced and simplified routine maintenance

**Starting at**  
**\$54,270 USD\***

### Special Offers

**Pay as low as 0% for up to 48 months\* PLUS receive a \$3,000 USD\*/\$3,900 CAD\* rebate or choose a \$5,500 USD\*\*/\$7,200 CAD\*\* cash rebate in lieu of financing on a Bobcat E35 compact excavator.**

[Build & Quote](#)

[Contact Dealer](#)

[View Offers](#)

[Find Dealer](#)[Download Brochure](#)

## E35 Overview

- In addition to its unrestricted rotation, the E35 features the exclusive Bobcat in-track frame for a compact footprint and leading jobsite maneuverability.
- Like all Bobcat machines, the E35 is designed to make routine maintenance easy. Its smart design gives you easy access to critical components.
- Option up for more versatility with performance-boosting features including a clamp-ready extendable arm, a long arm and an angle blade.

## E35 Specs & Compare

E35 Key Specifications			
E35	E35 (25 hp, Extendable Arm)	E35 (25 hp, Long-Arm)	
<b>Operating Weight</b>			
7,659 lb	8,590 lb	8,362 lb	
<b>Bucket Digging Force</b>			
7,284 lbf	7,284 lbf	7,284 lbf	
<b>Maximum Reach at Ground Level</b>			
204.3 in	235.1 in	215.8 in	
<b>Width</b>			
69.7 in	69.7 in	69.7 in	
<b>Tail Swing Type</b>			
Zero	Minimal	Minimal	
Engine			
E35	E35 (25 hp, Extendable Arm)	E35 (25 hp, Long-Arm)	
<b>Emissions Tier (EPA)</b>			
Tier 4	Tier 4	Tier 4	
<b>Engine Fuel</b>			
Diesel	Diesel	Diesel	
<b>Maximum Governed RPM</b>			
2,450 rpm	2,450 rpm	2,450 rpm	
<b>Turbocharged Engine</b>			
no	no	no	
<b>Optional Turbocharged Engine</b>			

N/A	N/A	N/A
<b>▲ Performance</b>		
E35	E35 (25 hp, Extendable Arm)	E35 (25 hp, Long-Arm)
<b>Operating Weight</b>		
7,659 lb	8,590 lb	8,362 lb
<b>Weight Class</b>		
3.5 t	3.9 t	3.8 t
<b>Travel Speed - High</b>		
2.9 mph	2.9 mph	2.9 mph
<b>Travel Speed - Low</b>		
1.6 mph	1.6 mph	1.6 mph
<b>Arm Digging Force</b>		
4,690 lbf	4,592 lbf	4,074 lbf
<b>Bucket Digging Force</b>		
7,284 lbf	7,284 lbf	7,284 lbf
<b>Rated Lift Capacity</b>		
3318 lb	3058 lb	3206 lb
<b>Lift Radius</b>		
118 in	118 in	118 in
<b>Boom Swing - Left</b>		
75°	75°	75°
<b>Boom Swing - Right</b>		
55°	55°	55°
<b>Maximum Dig Depth</b>		
121.2 in	153.2 in	133 in
<b>Max Dump Height</b>		
137.2 in	154.5 in	144.3 in
<b>Maximum Reach at Ground Level</b>		
204.3 in	235.1 in	215.8 in
<b>▲ Capacities</b>		
E35	E35 (25 hp, Extendable Arm)	E35 (25 hp, Long-Arm)
<b>Fuel Tank</b>		
13.7 gal	13.7 gal	13.7 gal
<b>▲ Hydraulic System</b>		
E35	E35 (25 hp, Extendable Arm)	E35 (25 hp, Long-Arm)
<b>Auxiliary Std Flow</b>		
16.9 gal/min	16.9 gal/min	16.9 gal/min

Auxiliary Pressure		
2,987 psi	2,987 psi	2,987 psi

**Dimension**

E35	E35 (25 hp, Extendable Arm)	E35 (25 hp, Long-Arm)
<b>Length</b>		
190 in	190.4 in	190.1 in
<b>Overall Length in Travel Position</b>		
190 in	190.4 in	190.1 in
<b>Width</b>		
69.7 in	69.7 in	69.7 in
<b>Height</b>		
96.2 in	96.2 in	96.2 in
<b>Height with Operator Cab</b>		
96.2 in	96.2 in	96.2 in

**Features**

E35	E35 (25 hp, Extendable Arm)	E35 (25 hp, Long-Arm)
<b>Air Conditioning</b>		
Optional	Optional	Optional
<b>Cab Enclosure</b>		
Optional	Optional	Optional
<b>Cab Heater</b>		
Not Applicable	Not Applicable	Not Applicable
<b>Heater Air Conditioning</b>		
Optional	Optional	Optional
<b>Radio</b>		
Optional	Optional	Optional
<b>Tail Swing Type</b>		
Zero	Minimal	Minimal
<b>Engine Shutdown</b>		
Standard	Standard	Standard
<b>Auxiliary Hydraulics</b>		
Standard	Standard	Standard
<b>Secondary Auxiliary Hydraulics</b>		
Optional	Optional	Optional
<b>Quick Tach System</b>		
Standard	Optional	Standard
<b>Rubber Track</b>		
Standard	Standard	Standard

Selectable Auxiliary Hydraulic Flow		
Standard	Standard	Standard
Angle Blade		
Optional	Optional	Optional

# E35 Features & Benefits

[Expand all](#) ▾

- ▾ **Performance** 13
- ▾ **Comfort** 2
- ▾ **Uptime Protection** 9
- ▾ **Serviceability** 2
- ▾ **Digital Connectivity** 1

## REGION SELECTOR

 **NORTH AMERICA (EN)**

## EMAIL SIGN-UP

**BUYING TOOLS**

**COMPANY**

**BUILD & QUOTE**

**ABOUT US**

**SEARCH INVENTORY**

**INNOVATION**

**FIND A DEALER**

**COMMUNITY**

**SPECIAL OFFERS**

**PEOPLE**

**REQUEST A DEMO**

**BOBCAT STORIES**

**CONTACT A DEALER**

**AMBASSADORS**

**BUYING RESOURCES**

**CONTACT US**

**LEGAL**

**CUSTOMER SERVICE**

**PRIVACY POLICY**

**WEBSITE FEEDBACK**

**TERMS & CONDITIONS**

**DEALER OPPORTUNITIES**

**RECALLS**

**GOVERNMENT SALES**

**FREQUENTLY ASKED QUESTIONS**



*One Tough Animal.*



**Bobcat Company is a member of the Doosan Group.** Doosan is a global leader in construction, grounds maintenance and material handling equipment, power and water solutions, and engineering that has proudly served customers and communities for more than a century.

Bobcat®, the Bobcat logo, the colors of the Bobcat machine and various other product names referenced on this website are trademarks of Bobcat Company in the United States and various other countries.

©2024 Bobcat Company. All rights reserved.